

Standart Tip Kablo Kanalları

B (Taban)	Yükseklik (H)	Ebatlar (mm)			Kesit (mm ²)	Sipariş Kodu	Birim Fiyat ₺/mt.	Ambalaj Miktarı mt.
		Diş Arası (E)	Diş Kalınlığı (F)					
15	30	5	7,5	340	T1 15x30 G	14,20	64	
25	30	5	7,5	610	T1-N 25x30 G	16,20	72	
25	40	4	6	820	T1-EN 25x40 G	16,10	72	
40	40	4	6	1360	T1-EN 40x40 G	23,20	40	
60	40	4	6	1970	T1-EN 60x40 G	36,40	24	
80	40	4	6	2680	T1-EN 80x40 G	41,30	24	
100	40	4	6	3380	T1-EN 100x40 G	54,70	16	
25	60	4	6	1190	T1-EN 25x60 G	27,10	48	
40	60	4	6	2040	T1-EN 40x60 G	31,30	36	
60	60	4	6	3080	T1-EN 60x60 G	40,20	24	
80	60	4	6	4150	T1-EN 80x60 G	50,30	24	
100	60	4	6	5250	T1-EN 100x60 G	64,20	16	
120	60	4	6	6300	T1-EN 120x60 G	78,20	16	
25	80	4	6	1550	T1-EN 25x80 G	38,40	48	
40	80	4	6	2700	T1-EN 40x80 G	41,20	32	
60	80	4	6	4140	T1-EN 60x80 G	53,50	24	
80	80	4	6	5660	T1-EN 80x80 G	63,10	24	
100	80	4	6	7150	T1-EN 100x80 G	87,60	16	
120	80	4	6	8630	T1-EN 120x80 G	96,20	16	
25	100	4	6	1750	T1-EN 25x100 G	57,40	16	
40	100	4	6	3310	T1-EN 40x100 G	57,10	16	
60	100	4	6	5140	T1-EN 60x100 G	68,00	8	
80	100	4	6	7020	T1-EN 80x100 G	84,70	8	
100	100	4	6	8920	T1-EN 100x100 G	150,70	8	
150	100	4	6	13570	T1-N 150x100 G	215,30	8	

Halojen Free Kablo Kanalları

B (Taban)	Yükseklik (H)	Ebatlar (mm)			Sipariş Kodu	Birim Fiyat ₺/mt.	Ambalaj Miktarı mt.
		Diş Arası (E)	Diş Kalınlığı (F)				
25	40	4	6	HF25X40SG2N	211,10	96	
40	40	4	6	HF40X40SG2N	287,00	64	
40	60	4	6	HF40X60SG2N	387,50	24	
40	80	4	6	HF40X80SG2N	416,20	32	
40	100	4	6	HF40X100SG2N	523,90	32	
60	80	4	6	HF60X80SG2N	523,90	24	
60	100	4	6	HF60X100SG2N	732,00	24	
80	80	4	6	HF80X80SG2N	732,00	16	
80	100	4	6	HF80X100SG2N	918,50	16	
100	100	4	6	HF100X100SG2N	1.219,90	16	

Malzeme: Alev iletmez PC/ABS karışımı (**Bromit, klor ve flor gibi zararlı malzemeler içermez**)

EN50085-2-3, UL-94V0, RoHS, DIN 43659 şartlarını sağlar.

Renk: Gümüş gri



Esnek Kablo Kanalları

B (Taban)	Yükseklik (H)	Boy / Ad.	Kesit (mm ²)	Sipariş Kodu	Birim Fiyat ₺/Adet	Ambalaj Miktarı Ad.
17,5	23,0	50 cm	275	DN-AS G	41,60	24
32,0	38,5	50 cm	900	DN-AM G	55,60	24
42,5	48,5	50 cm	1550	DN-AL G	69,10	14

DN-A